



GL-8PAR20-3040-V4 LIGHTING SPECS
Light Output (Lumens) 600Lm ± 10%
Power 8 Watts
Lumens per Watt (Efficacy) 75
Colour Accuracy (CRI) 80+
Light Colour 3000k Warm White
LED Chip Bridgelux
Size Ø 62*80 (2 ^{1/2} " x 3 ^{1/8} ")
Beam Angle 40°
Dimmable
Energy Star Rating
25,000 Life Hours
10 Year Warranty



Lighting Specs	PAR20
ITEM NO.	GL-8PAR20-3040-V4
Light Output (Lumens)	600
Watts	8
Lumens per Watt (Efficacy)	75
Colour Accuracy	80+
Colour Rendering Index (CRI)	
Light Colour	3000K (Warm White)
	
2700K 3000K 4500K 6500K	
8 Watt Warm White	

GL-8PAR20-3040-V4 PHOTO METRICS			
MOUNTING HEIGHT	CENTER BEAM FOOT CANDLES (FC)	EDGE OF BEAM FOOT CANDLES (FC)	BEAM AREA COVERED
4FT	53.6FC	18.3FC	3'
6FT	24FC	8.1FC	4' 6"
8FT	13.3FC	5.9FC	6"
10FT	8.1FC	2.6FC	8'
12FT	5.6FC	1.9FC	9' 6"
14FT	3.6FC	1.3FC	11'
16FT	2.7FC	1.1FC	12'6"