



SPECIFICATIONS:

Light Output: 1400 LM/m (430 LM/ft.)
 Power: 14 Watts/m (4.3 Watts/ft.)
 Voltage: 12V
 Efficacy (Lumens per Watt): 100 LM/W
 Colour Accuracy (CRI): 80+
 Light Colour: 3000K Vibrant Warm White
 Beam Angle: 120°
 Length: 16'-3" / 5m
 Width: 0-3/8" / 10mm
 Depth: 0-1/8" / 3mm
 Cuttable every 1.5" / 38mm
 Dimmable
 IP20 (Indoor Use)
 50,000 Life Hours
 Included: 4 x Silicone End Caps per Roll

LIGHTING FACTS

HIGH DENSITY LED RIBBON

ITEM NO. GL-HD-DS-12V-30K-IP20

Light Output (Lumens)	1400/M
Watts	14/M
Lumens per Watt (Efficacy)	100

Colour Accuracy	80+
Colour Rendering Index (CRI)	

Light Colour 3000K Vibrant Warm White



2700K 3000K 3500K 4000K 4500K 5000K 6000K
14 Watt/m • Vibrant Warm White





HIGH DENSITY LED RIBBON (DOTLESS IP20) PART NUMBER: GL-HD-DS-12V-30K-IP20

PRODUCT BENEFITS:

This high density ribbon is perfect for many indoor applications as this ribbon looks seamless and has no dots like many others!

AVAILABLE ACCESSORIES:

12V Dimmable Drivers

25W • GLS-12025-TD
50W • GLS-12050-TD
100W • GLS-12100-TD
150W • GLS-12150-TD
200W • GLS-12200-TD

Quick Connect

GLF-CUBE-FEED-12V (5 Pack)

Quick Connect Feed

GL-TODIP20-FEED

Quick Connect Flexible Joiner

GL-TODIP20-FLEX

Quick Connect Joiner

GL-TODIP20-JOINER

Quick Connect "L" Joiner

GL-TODIP20-L

Aluminum Channels

(Available in aluminum, white and black with black lens)

Deep Recess • GLF-1201REC-1M
Deep Surface • GLF-1202SUR-1M
45° Angle • GLF-1203ANG-1M
Shallow Recess • GLF-1204RECS-1M
Shallow Surface • GLF-1205SURS-1M

Drywall Channel Lighting System

Chopstick Lighting System