




SPECIFICATIONS:

Light Output: 1400 LM/m (430 LM/ft.)
 Power: 14 Watts/m (4.3 Watts/ft.)
 Voltage: 12V
 Efficacy (Lumens per Watt): 100 LM/W
 Colour Accuracy (CRI): 80+
 Light Colour: 3000K Vibrant Warm White
 Beam Angle: 120°
 Length: 16'-3" / 5m
 Width: 0-3/8" / 10mm
 Depth: 0-3/16" / 4mm
 Cuttable every 1.77" / 45mm
 Dimmable
 Waterproof IP67 (Waterproof)
 50,000 Life Hours
 Included: 4 x Silicone End Caps per Roll

LIGHTING FACTS

HIGH DENSITY LED RIBBON

ITEM NO.	GL-HD-DS-12V-30K-IP67
Light Output (Lumens)	1400/M
Watts	14/M
Lumens per Watt (Efficacy)	100
Colour Accuracy	80+
Colour Rendering Index (CRI)	
Light Colour	3000K Vibrant Warm White
	
2700K 3000K 3500K 4000K 4500K 5000K 6000K	
14 Watt/m • Vibrant Warm White	

PHOTOMETRICS:



PRODUCT BENEFITS:

This high density ribbon is perfect for many applications indoor and out! Great for areas that may be exposed to moisture or where the ribbon is visible, as this ribbon looks seamless and has no dots like many others!

AVAILABLE ACCESSORIES:**12V Dimmable Drivers**

25W • GLS-12025-TD
50W • GLS-12050-TD
100W • GLS-12100-TD
150W • GLS-12150-TD
200W • GLS-12200-TD

Quick Connect

GLF-CUBE-FEED-12V (5 pack)

Quick Connect Feed

GL-PAXIP67-FEED

Quick Connect Flexible Joiner

GL-PAXIP67-FLEX

Quick Connect Joiner

GL-PAXIP67-JOINER

Aluminum Channels

(Available in aluminum, white and black with black lens)

Deep Recess • GLF-1201REC-1M
Deep Surface • GLF-1202SUR-1M
45° Angle • GLF-1203ANG-1M
Shallow Recess • GLF-1204RECS-1M
Shallow Surface • GLF-1205SURS-1M

Drywall Channel Lighting System**Chopstick Lighting System**